

OPL WHITE LABEL

PAN030TN0MZA20CTAA, PAN040TN0MZA20CTAA, PAN055TN0MZA20CTAA

XControl+ Cabinet Hardmount Washer-Extractor

FEATURES

- 200 G-Force
- Stainless steel cylinder and tub
- Anthracite gray front and side panels
- Soap box
- Large drain valve
- Front access to vital parts for easy maintenance

LIMITED WARRANTY

- 1-Year: door seal gaskets, water valve diaphragms, belts and internal hoses
- 5-Years: frame, cylinder shaft and bearings
- 3-Years: any parts not listed above



Fully programming XControl+

- 20 pre-set wash programs
- 99 programming cycles
- Graphical display

OPL WHITE LABEL - CABINET HARDMOUNT WASHER-EXTRACTOR SPECIFICATIONS

MODEL	PAN030TN0MZA20CTAA*	PAN040TN0MZA20CTAA*	PAN055TN0MZA20CTAA*
CAPACITY - lb (kg)	30 (13.5)	40 (18)	55 (24)
OVERALL WIDTH - in (mm)	29.53 (750)	35.03 (890)	35.03 (890)
OVERALL DEPTH - in (mm)	35.43 (900)	36.02 (915)	41.73 (1,060)
OVERALL HEIGHT - in (mm)	48.22 (1,225)	55.51 (1,410)	55.51 (1,410)
CYLINDER DIAMETER - in (mm)	24.40 (620)	29.53 (750)	29.53 (750)
CYLINDER DEPTH - in (mm)	17.72 (450)	16.14 (410)	21.46 (545)
CYLINDER VOLUME - in (mm)	4.8 (135)	6.4 (180)	8.5 (240)
DOOR OPENING SIZE - in (mm)	16.14 (410)	18.11 (460)	18.11 (460)
DOOR BOTTOM TO FLOOR - in (mm)	13.46 (342)	18.31 (465)	18.31 (465)
WATER INLET CONNECTION - in (mm)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)
DRAIN DIAMETER - in (mm)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)
DRAIN CENTER HEIGHT TO FLOOR - in (mm)	3.85 (98)	5.12 (130)	5.12 (130)
MOTOR POWER - HP (kW)	1 (0.75)	1.48 (1.1)	2.01 (1.5)
CYLINDER SPEED	Wash - RPM	46	42
	Extraction - RPM (G-Force)	760 (200)	690 (200)
VOLTAGE/ CIRCUIT BREAKER - FLA	(B) 120/60/1	20 - 13.3	-
	(Z) 200-240/60/1	10 - 7.2	15 - 9.1
SHIPPING DIMENSIONS APPROX. - in (mm)	Width	31.50 (800)	36.42 (925)
	Depth	37.4 (950)	38.19 (970)
	Height	53.35 (1,355)	61.02 (1,550)
NET WEIGHT - lb (kg)	419 (190)	695 (315)	728 (330)
STANDARD SHIPPING WEIGHT - lb (kg)	441 (200)	739 (335)	783 (355)
AGENCY APPROVALS	CSA	CSA	CSA

* 7.9" base available

For the most accurate information, the installation guide should be used for all installations, design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

